

## B 500 Pan Mixer

### **beba advantages:**

- excellent power transmission
- perfect for high-performance concrete or refractory material
- low dumping height - vertical adjustment (1490-1790mm)
- calm mixing during accurate mixing movement by two-way bearing of the main shaft
- very high torque for a powerful start to mixing
- forklift carriage
- the mixer is freely accessible and makes easy, comfortable filling possible over the protection cover - the mixing process can be observed very well
- the protection cover is hinged and has a safety disconnection
- the removable hand drawbar over quick-locking mechanisms is accommodated in a connector at the container
- extension cable with phase inverter (10m)
- air wheels over quick-locking mechanisms in front and in the back plug-on, when emptying e.g. a barrow can be stored crosswise
- emptying by segment side-gate for a fast, clean and well-proportioned emptying of the mixing material
- CE-conform in accordance to European Union machine guidelines



## B 500 options



B 500 in stainless steel



B 500 with charging hole,  
filling connection and  
pneumatic outlet



B 500 with mechanical  
bag filling



B 500 with dust cover

## B 500 Pan Mixer

Voltage:	3-phase	D 1:	1230 mm
Power:	7.5/11 KW, 3-phase	H 1:	650-950 mm
Mixing volume:	300 liters	H 2:	610 mm
Total volume:	500 liters	H 3:	540-840 mm
Weight:	450 kg	H 4:	460 mm
Speed:	42 rpm		

B 500 dimension sheet

